


Nylon Fully Insulated Male Disconnect Dimensions



| Wire Range (AWG) | Wire Range (mm ²) | Tab Size (in.) | Tab Size (mm) | Max. Wire Ins. Dia. (in.) | Max Wire Ins. Dia. (mm) | Dimensions (in.) | | | | Dimensions (mm) | | | | Cat. No |
|------------------|-------------------------------|----------------|---------------|---------------------------|-------------------------|------------------|------|------|------|-----------------|------|------|-----|----------------|
| | | | | | | L | B | W | F | L | B | W | F | |
| 22-18 | 0.5 - 1.0 | .250 x .032 | 6.35 x 0.8 | .150 | 3.8 | .906 | .433 | .250 | .303 | 23.0 | 11.0 | 6.35 | 7.7 | 83-9911 |
| 16-14 | 1.5 - 2.5 | .250 x .032 | 6.35 x 0.8 | .185 | 4.7 | .945 | .433 | .250 | .303 | 24.0 | 11.0 | 6.35 | 7.7 | 83-9921 |
| 12-10 | 4.0 - 6.0 | .250 x .032 | 6.35 x 0.8 | .244 | 6.2 | .984 | .512 | .250 | .303 | 25.0 | 13.0 | 6.35 | 7.7 | 83-9931 |

7105°C/300 Volts max.

