




# WIRE TERMINATION

WWW.IDEALIND.COM • 1-800-435-0705 CUSTOMER ASSISTANCE

## Vinyl Insulated Multi-Stack Disconnect Dimensions



Wire Range (AWG)	Wire Range (mm <sup>2</sup> )	Tab Size (in.)	Tab Size (mm)	Max. Wire Ins. Dia. (in.)	Max Wire Ins. Dia. (mm)	Dimensions (in.)						Dimensions (mm)						Cat. No.
						L	W	E	F	W1	F1	L	W	E	F	W1	F1	
22-18	0.5 - 1.0	.250 x .032	6.35 x 0.8	.150	3.8	.886	.413	.260	.315	.250	.323	22.5	10.5	6.6	8.0	6.35	8.2	<b>83-9611</b>
16-14	1.5 - 2.5	.250 x .032	6.35 x 0.8	.185	4.7	.886	.413	.260	.315	.250	.323	22.5	10.5	6.6	8.0	6.35	8.2	<b>83-7051</b>
12-10	4.0 - 6.0	.250 x .032	6.35 x 0.8	.244	6.2	.945	.512	.260	.315	.250	.363	22.5	13.0	6.6	8.0	6.35	8.2	<b>83-7081</b>

75°C/300 Volts max.