

VOLTAGE/CONTINUITY TESTERS

MEASURE/INDICATE AC/DC VOLTAGE

- cULus Listed (all models)
- CAT IV 600V & CAT III 600V options
- Digital Multifunction, Analog and Solenoid Models
- IP42 Dustproof/Water (61-557 & 61-547)
- 2 Meter drop protection (61-557 & 61-547)
- Lead holders are spaced to test tamper resistant outlets
- Bright LED flashlight, continuity, NCVT, GFCI test, LoZ (61-557)



61-557

Voltage and Continuity Tester w/LCD, GFCI, Flashlight & NCVT
6-600V AC/DC, CAT IV 600V



61-547

8 Level AC/DC Voltage Indicator with
Polarity Indicator
12-600V DC | 24-600V AC
CAT III 600V



61-076

Vol-Con® Voltage/Continuity Tester
5-600V AC/DC
CAT III 600V



61-065

Vol-Test® Voltage Tester
100-600V AC/DC
CAT III 600V



NCV

Flashlight

Backlit Display

NCV, Continuity,
High Voltage,
Visual Indications,
Augment Audible
Indications

GFCI Test

LoZ
Eliminates ghost
voltage
(induced voltage
from adjacent
conductors)

Uses Standard
Test Leads
(included)

Probe Holder
for Storage/
Measurement
(61-557, 61-547)

Universal Magnetic
Strap Clip
(61-557, 61-547)





Universal Magnetic
Strap Clip
(UMHS-757)

allows for two-handed
operation of probes with
tester suspended from
strap (61-557 & 61-547)
(sold separately)

THE ELECTRICIAN'S
CHAMPION™



VOLTAGE/CONTINUITY TESTERS AND VOLTAGE TESTERS

VOLTAGE TESTER SELECTION GUIDE	 NEW	 NEW		
	61-557	61-547	61-076	61-065
FEATURES				
CAT Rating (Safety)	CAT IV 600V	CAT III 600V	CAT III 600V	CAT III 600V
Listing Preferred	cULus, CE	cULus, CE	cULus	cULus
Drop Protection	6.6 ft. (2m)	6.6 ft. (2m)		
Ingress Protection	IP42	IP42	—	—
AC Voltage (Volts)	6 ~ 600	24 ~ 600	5 ~ 600	100 ~ 600
DC Voltage (Volts)	6 ~ 600	12 ~ 600	5 ~ 600	100 ~ 600
High Voltage Alarm	ACV >30 or DCV >30V	ACV/DCV >48V	—	—
Audible Continuity	✓	—	—	—
Visual Continuity	✓	—	✓	—
Backlight	✓	—	—	—
Low Impedance (LoZ)	✓	—	✓	✓
NCV	90-600V AC	—	—	—
Auto Ranging	✓	—	—	—
Magnetic Strap Mount	✓	✓	—	—
Test Probe Holder	✓	✓	✓	✓
Flashlight	✓	—	—	—
Auto-Power Off (APO)	✓	—	—	—
Low Battery Indicator	✓	—	—	—
Battery Type	3 x 1.5V AAA	—	4 x 1.5V LR44	—
LCD Display Count	600	—	—	—
Backlight	✓	—	—	—
DC Polarity Indication	✓	✓	✓	—
Leads	Removable	Fixed	Removable	Removable
GFCI Test	✓	—	—	—
Display	LCD	Neon Lamps	Indicator Movement	Indicator Movement
Warranty	2-Year*	2-Year*	2-Year*	2-Year*
ACCESSORIES				
Test Leads	TL-757	—	61-070	61-070
Magnetic Hanging Strap	UMHS-757	UMHS-757	—	—



Scan with your smartphone to learn more



Probe Holders are spaced to test tamper resistant outlets (61-557 & 61-547)



Continuity Testing (61-557 & 61-076)



Backlit Display and Flashlight (61-557)



NCVT in tip detects presence of AC voltage (61-557)



Tests GFCI protected circuits (61-557)



LoZ option to eliminate ghost voltage (61-557)

P-6045 (5-21)
©2021 IDEAL INDUSTRIES, INC.

Specifications are subject to change without notice.

IDEAL CUSTOMER SERVICE:
orderdesk@idealindustries.com
1-800-824-3325
www.idealind.com

THE ELECTRICIAN'S
CHAMPION™

