

## **Pro-Pull™ Measuring Pull Tape**

A tape made from woven polyester fiber and printed with sequential footage markings. This tape is approximately 0.50" wide and supports a tensile strength of 1,250 lbs. Packaging of this tape is available in reel form only.



## **Technical Characteristics**

Tensile Strength	1,250 lb.
Working Load	1,250 lb.
Color	White with black print
Tape Width	0.50" +/- 0.05"
Tape Thickness	0.037" +/- 0.007"
Weight	6.5 lbs. per 1,000 ft.
Packaging	Reel with UV resistant white
	plastic wrap

Part Number	Description
31-1250-10	1,250 lb., 1,000 ft. reel
31-1250-30	1,250 lb., 3,000 ft. reel
31-1250-50	1,250 lb., 5,000 ft. reel

## Features & Benefits

- Highly legible sequential footage markings
- Increased efficiency, measure and pull in a single step
- Enhanced softness reduces hand damage
- High quality standards including lot tracing
- Pre-lubricated with silicone for easy payout
- Abrasion resistant, low stretch fiber
- Rot/mildew resistant, can be left in conduit for future use

1250 IDEAL Pro-Pull™ 05/24/21 TC 0137 FT

1250 IDEAL Pro-PullTM MM/DD/YY ZZ XXXX

MM/DD/YY - DATE OF RUN (MONTH/DAY/YEAR) XXXX - FOUR DIGIT SEQUENTIAL FOOT LENGTH MARKING ZZ - LOT TRACKING CODE