

Pro-Pull™ Measuring Pull Tape

A tape made from woven polyester fiber and printed with sequential footage markings. This tape is approximately 0.25" wide and supports a tensile strength of 400 lbs. Packaging of this tape is available in bucket form only.



Technical Characteristics

Tensile Strength	400 lb.
Working Load	400 lb.
Color	White with black print
Tape Width	0.25" +/- 0.0625"
Tape Thickness	0.034" +/- 0.007"
Weight	2.4 lbs. per 1,000 ft.
Packaging	White bucket with lid

Part Number	Description
31-400B-45	400 lb., 4,500 ft. bucket

Features & Benefits

- Highly legible sequential footage markings
- Increased efficiency, measure and pull in a single step
- Enhanced softness reduces hand damage
- High quality standards including lot tracing
- Pre-lubricated with silicone for easy payout
- Abrasion resistant, low stretch fiber
- Rot/mildew resistant, can be left in conduit for future use

400 IDEAL Pro-PullTM 05/10/21 JC 0837FT

400 IDEAL Pro-Pull™ MM/DD/YY ZZ XXXX

MM/DD/YY - DATE OF RUN (MONTH/DAY/YEAR) XXXX - FOUR DIGIT SEQUENTIAL FOOT LENGTH MARKING ZZ - LOT TRACKING CODE